TOM-M5 Touch Monitor

rugged, compact, priced right



TOM-M5 is more than a touchmonitor. Designed specifically for touch applications, TOM-M5 sits on a sturdy base and is sealed against spills. It allows additional devices to be integrated neatly, without extra cables or power supplies. Add-on devices are magnetic card reader, barcode slot reader, fingerprint reader, and rear customer display.

TOM-M5 offers different touch technologies to fit into your application and budget requirements. Choose Resistive, Intellitouch, or Infra Red. With its built-in 4 USB ports, you can now easily connect keyboard, barcode scanner, and printer to TOM-M5, instead of reaching under or behind the counter for the PC ports.

Ideal for point-of-sales, kiosks, industrial control, gaming, healthcare. With its multiple benefits and competitive prices, TOM-M5 gives you more value than other touchmonitors.

Specifications

•••••••		
Touchscreen	USB: Resistive, Projective Capacitive	
Display	15" LCD, Active matrix TFT	
Resolutions	1024x768 (optimal), 800x600, 640x480	
Colors	16.2 millions	
LCD Brightness	350 NIT	
Input video signal	Analog VGA DB15, or DVI	and the second se
Driver Support	Windows 7, POS 7, Windows 8.1, Linux	connect USB here
Viewing Angle	Left 70° /Right 70°, Up 60°/ Down 65°	
Operating Temperature	0° C to 40° C	
Operating Humidity	20% to 80%	
Backlight Life	50,000 hours (min) to half brightness	
Menu Buttons (OSD)	On the side, lock-able	
Bezel Color	Black, White	VESA mount
Dimensions	Width: 14.63" (380mm)	
	Height: 14" (364mm)	
	Depth: 9" (234mm)	
Weight	15 lbs / 6.9 kgs (9 lbs / 4.1 kgs without base)	
Mounting Options	Wall or Pole mount, VESA 75mm	
Security Lock	Bolted (4mm screw), or Kensington MicroSaver	
Ports/Connectors	1 x 15-Pin VGA	MSR and/or Fingerprint reader Rear display
	1 x DVI	Fingerprint reader Rear display
	4 x USB 2.0	
	1 x DC Out +12V	
Audio (optional)	Internal speakers (2)	
Power Supply	External, AC 100-240V, DC Out +12V, 5A	
Agency Approvals	FCC A, CE, UL	
Manufacturer's Part No	1M100021B1 (Resistive)	
	1M1000F2B1 (Projective Capacitive)	Product by
Add-ons	Internal speakers, 2 watts/channel	i louder by
	Magnetic stripe reader (MSR), USB	Pioneerpos, II
	Fingerprint reader, USB	www.pioneerpos.com
	2x20 Customer display, or 10.1" LCD	888.468.9757